




## BOLPT21BC-B

Bloomsbury Ovolo Light Oak 1 gang 20AX 2 Way Toggle Bright Chrome Plain Dome/Black Collar

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |                              |    |
| Primary Range   | Bloomsbury  |   |
| Insert Type   | 2 Way Toggle  |   |
| Plate Finish  | Bloomsbury Ovolo Light Oak  |   |
| Insert Colour   | Bri Chr Plain Dome/Black Colar  |   |
| Minimum Wall Box Depth  | 25mm  |   |
| Switched Poles  | Single  |   |
| Current Rating  | 20AX  |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 20 Amp inductive  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Terminal Capacity 3   | 2 x 2.5mm <sup>2</sup>  |   |
| Terminal Capacity 4   | 2 x 4mm <sup>2</sup> Multi-strand   |   |
| Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 6 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 5 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 2 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN 60669-1   |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 03 April 2017 11:51 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84

