

Item Image

VW TCS W
 Vogue White 1 gang Telephone Slave. Standard Insert will be White.
 A tough, scratch resistant finish with inherent antimicrobial properties.


Primary Range	Vogue White
Insert Type	LJ Telephone Slave Outlets
Plate Finish	Vogue White moulded high-grade thermoset plastic
Frame Finish	
Switch Colour	
Body & Switch Trim	Vogue White
Height	Single = 86mm
Width	Single = 86mm
Depth	Single = 6.8mm
Fixing Hole Centres	Box Fixing = 60.3mm
Minimum Wall Box Depth	25mm
Wattage	
Switched Poles	N/A
Current Rating	
Voltage	
Max load	
Contact Gap Minimum	N/A
Terminal Capacity 1	
Terminal Capacity 2	
Terminal Capacity 3	
Terminal Capacity 4	
Terminal Capacity 5	
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-Strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40° C
Recommended Location	Indoor use only
Standard/Approval	

Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires
1	GREEN / White
2	BLUE / White
3	ORANGE / White
4	WHITE / Orange
5	WHITE / Blue
6	WHITE / Green

Main Wire Colour shown in CAPITALS

Incoming Telephone Cable
 On 4 wire systems, Pin 1 and 6
 are not connected.



The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.

Additional Features:

Inline terminals.
 Screw caps supplied to conceal the fixing screws.

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality Management System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at May 2015 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK
 T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com
 www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • J Berry • AMH Hamilton (Secretary)
 Registered Office: 78 Tenter Road • Moulton Park • Northampton • NN3 6AX
 Registered in London No. 941624 • VAT Registration No. 222 6607 84

