



Contour Metal Consumer Unit

Amendment 3 Compliant

Stylish Design

Designed with your customers in mind the Contour consumer unit comes with a curved and flush lid and is finished in an attractive matt white.

Safety First

For that extra level of safety and protection against fire Hamilton's consumer units can be fitted with intumescent gland adaptors. The intumescent strips expand when they are exposed to heat, containing the fire within the enclosure. The consumer units also have a fail safe drop down lid and are fully compliant to BS7671 amendment 3.

Ease of Installation

All of the Hamilton consumer units come with features that make installation simple. The cable entries are positioned for easy access to devices, they have large, accessible wiring space with multiple fixing points and fully flexible neutral configurations. There are also removable gland plates on the top and bottom of the consumer units.

Fit and Forget

All our consumer units are produced to a high standard making them tough and scratch resistant. Plus they all come with a two year guarantee for that extra peace of mind.



Optimised
Safety



Fully
Compliant



Easy
Installation




Product
Guarantee

Product Features:

- Full compliance to BS 7671 (Amendment 3)
- Complete with UNIQUE fire retardant trunking adaptors (50x50mm and flush fitting, one of each)
- Robust metal enclosures include removable gland plates on top and bottom and knockouts to rear
- Solid metal drop down visor
- Neutral and earth terminals at the top of enclosure
- Flexible neutral connection allows varied configurations of protected/unprotected ways
- Large and accessible wiring space
- Raised DIN rail allows for top and bottom wiring entries
- Full 35mm DIN rail
- Enclosure finished in matt white
- 2 Year product guarantee
- Standard BS EN 61439-3

Product Features:

- Assembled Metal Consumer Unit – BS EN 61439-3
- 100A 230V AC 50Hz DP Main Switch – BS EN 60947-3
- 80A 30mA DP RCD – BS EN 61008
- IP Rating – Front IP2X, Top IP4X

See it for yourself on 

MAIN SWITCH INCOMER

Sales Code	Rating	No. Usable Ways
HLCMCU8MSW	100A	8
HLCMCU12MSW	100A	12
HLCMCU14MSW	100A	14
HLCMCU16MSW	100A	16
HLCMCU20MSW	100A	20

RCD INCOMER

Sales Code	RCD Rating	No. Usable Ways
HLCMCU8RCD	80A 30mA	8
HLCMCU12RCD	80A 30mA	12
HLCMCU14RCD	80A 30mA	14
HLCMCU16RCD	80A 30mA	16
HLCMCU20RCD	80A 30mA	20

HIGH INTEGRITY/DUAL RCD

Sales Code	RCDs	Rating	No. Usable Ways
HLCMCU8HI	2 x 80A 30mA	100A	8 Configurable
HLCMCU10HI	2 x 80A 30mA	100A	10 Configurable
HLCMCU12HI	2 x 80A 30mA	100A	12 Configurable
HLCMCU16HI	2 x 80A 30mA	100A	16 Configurable

SPLIT LOAD

Sales Code	RCD	Rating	No. Usable Ways
HLCMCU10SPL	1 x 80A 30mA	100A	10 Configurable
HLCMCU12SPL	1 x 80A 30mA	100A	12 Configurable
HLCMCU14SPL	1 x 80A 30mA	100A	14 Configurable
HLCMCU18SPL	1 x 80A 30mA	100A	18 Configurable



A large selection of Circuit Protection Modules are also available - please see the full brochure for details.

GLAND ADAPTORS

Sales Code	Description
HLMGA40X25	Gland adaptor 40x25mm
HLMGA50X50	Gland adaptor 50x50mm
HLMGAFLUSH	Gland adaptor flush fitting



Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter information, designs and dimensions without prior notice. All products listed conform to current British or European standards and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.