



PAIR OF 5¼" WHITE CEILING SPEAKERS 75W 8 OHMS
Indoor Use Only



Woofers:	133mm, 5¼" kevlar or polypropylene, rubber surround	Sensitivity:	89 dB @ 1W / 1M
Tweeter:	19mm, ¾" Ferrofluid cooled silk dome in swivel mount +/-3dB treble switch	Impedance:	8 Ohms
Power handling:	75 Watts	Dimension (Dia):	205 x 64mm 8¼" x 2½"
Frequency:	Response: 60 - 20000 Hz	Cutout size (Dia):	180 mm 7⅛"
		Mounting depth:	61 mm 2⅞"

SINGLE 6½" WHITE STEREO CEILING SPEAKER 100W 8 OHMS
Indoor Use Only



Woofers:	Dual voice coil, 165mm, 6½" kevlar or polypropylene, rubber surround	Sensitivity:	89 dB @ 1W / 1M
Tweeter:	Dual 19mm, ¾" Ferrofluid cooled silk dome +/-3dB Treble Switch	Impedance:	8 Ohms
Power handling:	100 Watts	Dimension (Dia):	234 x 74mm 9¼" x 2⅞"
Frequency:	Response: 30 - 20000 Hz	Cutout size (Dia):	208mm, 8⅛"
		Mounting depth:	70mm, 2¾"

PAIR OF 4" WHITE SPEAKERS 50W 8 OHMS
Indoor and Outdoor Use. 2-way, weather resistant



Woofers:	102mm, 4" Polypropylene	Sensitivity:	88 dB @ 1W / 1M
Tweeter:	19mm, ¾" Polycarbonate, fluid-cooled	Impedance:	8 Ohms
Power handling:	50 Watts	Housing:	Polypropylene with aluminium grille
Frequency:	Response: 50 - 20,000Hz	Dimension:	135 x 205 x 136 mm 5⅝" x 8⅛" x 5⅜"

Note: All speakers must be installed to comply with current building regulations

mercury
 multi-room audio and lighting control Systems